

PLS puck

HIGHLIGHTS

- Operational range of 20 m in free field
- Signaling via 3 RGB LEDs, vibration alarm, and acoustic signal



Overview

CHASSIS	Dimensions (HxWxD)	61x61x16 mm
	Weight	37 gr
	Protection class	IP 22
ENERGY MANAGEMENT	Battery	3 x 1000 mAh
COMMUNICATION	Radio	Frequency: 2.4 GHz BLE
	Operational range	20m in free field
	Signalling	3 RGB LEDs Vibration alarm Acoustic signal
	Chip	nRF52 Series flash-based SoC, Bluetooth 5, NFC, Sensitivity of -96 dbm for BLE
CERTIFICATIONS	CE	

Locate – Communicate – Simplify

The puck pinpoints customers in real-time precisely in the room and enables in situ service.

Benefit from more accurate and faster service!

Furthermore, the puck interacts with the customer. The signaling is effected via 3 RGB LEDs, vibration alarm, and acoustic signals. The puck is able to show any desired message on the display.

Benefit from real-time communication and keep everyone up to date!

The puck is the smart way to optimize routes and automate your order management!

The puck makes sure that everyone gets faster what is needed.

Benefit from accelerated service and higher customer satisfaction!

PLS puck

Dimensions (in mm)

Figure shows configuration variant

